

CP Series

Flame Retardant Case



Dichroic Halogen



Tungsten Halogen

Specification

- Mode of Operation : Non - Maintained
- Lamp : Tungsten Halogen or Dichroic Halogen, with 180° adjustable sets and plastic-cover anti-dust
- Main Supply Construction : AC 220 Volt, 50 Hz, ±10% - Single Phase
- : Electro-Galvanized steel sheet 1 mm. with epoxy powder and stove enamel coated anti-rust corrosion proof or **ABS Flame Retardant UL 94 V - O**
- Battery : Sealed lead acid battery, based on ISO 9001, ISO 14001 certified and UL
- Charger : Solid state system automatic battery charger
- : Constant voltage & current charging systems
- : **SMD electronic part**
- : **Switching regulated transformer**
- Charging Period : 15-20 Hours as required
- Safety Features :
 - Low - High voltage cut-off, preventing battery over charge & discharge
 - AC fuse - preventing short circuit and overload for main incoming AC 220 Volt
 - DC fuse - preventing short circuit and overload for charging & load
 - AC under voltage protection

CP Series

Dichroic Halogen (Square)

MODEL	BATTERY	BULBS (Watt)	DURATION (Hrs. Mins) ±10%	WEIGHT (Kgs)	DIMENSION W x L x H (cm)
CP 07	12V.7.2Ah.	2 x 20	1.30	4.6	29.5 x 8.5 x 28
		2 x 35	1.00		
CP 18	12V.18Ah.	2 x 35	2.00	8.1	37 x 8.5 x 34
CP 23	12V.24Ah.	2 x 50	2.00	10.0	
CP 26	12V.26Ah.	2 x 55	2.00	12.4	
CP 35	12V.35Ah.	2 x 50	3.00	14.2	37 x 18 x 34
CP 40	12V.40Ah.	2 x 55	3.00	19.1	

Tungsten Halogen Lamp (Rectangle □ / Round ○)

MODEL	BATTERY	BULBS (Watt)	DURATION (Hrs. Mins) ±10%	WEIGHT (Kgs)	DIMENSION W x L x H (cm)
○ CP 07	12V.7.2Ah.	2 x 35	1.0	5.1	29.5 x 8.5 x 28
□ CP 18	12V.18Ah.	2 x 35	2.0	8.4	37 x 8.5 x 34
□ CP 23	12V.24Ah.	2 x 50	2.0	10.0	
□ CP 26	12V.26Ah.	2 x 55	2.0	12.4	
□ CP 35	12V.35Ah.	2 x 50	3.0	14.7	37 x 18 x 34
□ CP 40	12V.40Ah.	2 x 55	3.0	19.1	

Remarks : Halogen Round Type use for CP-07 Only