

# TUBE Series

## Compact-slim Type

**new**



EXB 111 PL-S

### Wall Box Type



EXB 112 PL-S

### Specification

- Mode of Operation : Maintained
- Lamp : PL lamp
- Main Supply : AC 220 Volt, 50 Hz, ±10% - Single Phase
- Construction : Electro-Galvanized steel sheet 1 mm. with epoxy powder and stove enamel coated anti-rust corrosion proof
- Battery : Sealed lead acid battery, based on ISO 9001, ISO 14001 certified and UL
- Chargers : Solid state system automatic battery charger  
: Constant voltage & constant current charger  
: SMD electronic part  
: Switching regulate transformer
- Charging Period : 10-20 Hours as Required
- Safety Features : Low - High voltage cut-off, preventing battery over discharge and recharge  
: AC fuse - preventing short circuit and overload for main incoming AC  
: DC fuse - preventing short circuit and overload for charging
- Legend : ISO Green, other legend optional are available
- Mounting : Wall or Ceiling mounted

### Wall Box Type

MODEL	SIDE	BATTERY	BULBS (Watt)	DURATION (Hrs.) ±10%	DIMENSION W x L x H (cm)
EXB 111 PL-S	1	6V.4.2Ah.	PL 11 W x 1	2.0	6.5 x 38 x 18.5
EXB 112 PL-S	2				7.0 x 38 x 18.5

### Standard Legend



D-2110



D-2111



E-000



D-323



D-2112



D-2113



D-008



D-953