

LED Series Exit Sign Light Built-in Series

LED Series

Specification

Mode of Operation :	Maintained	Wall Box Type
Lamp :	LED	
Lamp life time :	100,000 hours.	
Main Supply :	AC 220 Volt, 50 Hz, $\pm 10\%$ - Single Phase	
Construction :	Electro-Galvanized steel sheet 1 mm. with epoxy powder and stove enamel coated anti-rust corrosion proof or ABS casing	
Battery :	Nickle Metal Hydride Battery, High Temperature type	
Charger :	Solid state system automatic battery charger	
Charging Period :	10-24 Hours as required	
Safety Features :	Low - High voltage cut-off, preventing battery over discharge and recharge	
	AC fuse - preventing short circuit and overload for main incoming AC	
	DC fuse - preventing short circuit and overload for charging	
Legend :	ISO Green, other legend optional are available	
Mounting :	Wall mounted or Ceiling mounted	



EXB111-LED



EXB112-LED

Slimline Type



EXB303T-ED Recess Mount



EXB303S-ED Ceiling Mount

Wall Box Type

MODEL	SIDE	BATTERY	BULBS (Watt)	LUMINOUS INTENSITY (mcd)	DURATION (Hrs.) $\pm 10\%$	DIMENSION W x L x H (cm)	WEIGHT (Kgs.)
EXB 111-LED	1	3.6V 1800mAh.	40 LED(white)	8,000	3.0	3.5 x 38 x 18.5	1.0
EXB 112-LED	2					4.0 x 38 x 18.5	1.2

Slimline Type

MODEL	SIDE	BATTERY	BULBS (Watt)	LUMINOUS INTENSITY (mcd)	DURATION (Hrs.) $\pm 10\%$	DIMENSION W x L x H (cm)	WEIGHT (Kgs.)
EXB 303S-ED	1	3.6V 1800mAh.	24 LED(white)	8,000	3.0	8 x 39 x 22.5	1.6
EXB 303T-ED	2						

Floor & Wall Built-in

Specification

Mode of Operation :	Maintained	new
Lamp :	LED	
Lamp life time :	100,000 hours.	
Main Supply :	AC 220 Volt, 50 Hz, $\pm 10\%$ - Single Phase	
Construction :	Cover Toughened glass sheet 10 mm. (IK08)	
	Stainless steel frame	
	High-grade aluminum ingot back box	
	Thickened silicon rubber glue	
	High-grade waterproof (IP65)	
Battery :	Nickle Metal Hydride Battery, High Temperature type	
Charger :	Solid state system automatic battery charger	
Charging Period :	10-24 Hours as Required	
Safety Features :	Low - High voltage cut-off, preventing battery over discharge and recharge	
	AC fuse - preventing short circuit and overload for main incoming AC	
	DC fuse - preventing short circuit and overload for charging	
Legend :	ISO Green, other legend optional are available	
Mounting :	Wall Built-In or Floor Built-in	

Wall Built-in Type



Wall Built-in Type EXB-WBI Floor Built-in Type EXB-FBI

MODEL	SIDE	BATTERY	BULBS (Watt)	LUMINOUS INTENSITY (mcd)	DURATION (Hrs.) $\pm 10\%$	DIMENSION W x L x H (cm)	WEIGHT (Kgs.)
EXB - WBI	1	3.6V 1800mAh.	24 LED(white)	8,000	3.0	6 x 30 x 18	2.6
EXB - FBI	1	3.6V 1800mAh.	24 LED(white)	8,000	3.0	ϕ x w = 26 x 10	2.5